

DRILLING LOG		DIVISION South Atlantic		INSTALLATION Jacksonville District		SHEET 1 OF 1	
1. PROJECT Ft. Pierce, FL, Shore Protection Project				10. SIZE AND TYPE OF BIT 2-1/2" Vibracore			
2. LOCATION (Coordinates or Station) X=1127,628 Y=751,531				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) Mean Low Water, -1.2' NGVD			
3. DRILLING AGENCY EXMAR				12. MANUFACTURER'S DESIGNATION OF DRILL Vibracore			
4. HOLE NO. (As shown on drawing title and file number) CB-STL-C26				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER M. Clarke				14. TOTAL NUMBER OF CORE BOXES			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 7/13/95 7/13/95			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -27.4 Ft.			
9. TOTAL DEPTH OF HOLE 7.0 Ft.				18. TOTAL CORE RECOVERY FOR BORING 79 %			
				19. SIGNATURE OF GEOLOGIST G. Zarillo, J. Vann			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-27.4	.0					-27.4	0
			SAND, poorly graded, medium to fine grained quartz and shell hash, gray-brown, (SP) 65% shell		C26-2.7		2.5
-32.8	5.4			79			5
-34.4	7.0		SAND, poorly graded, medium to fine grained quartz and shell hash, finer grained than -27.4 ft. to -32.8 ft., brown, (SP) 70% shell		C26-6.2		7.5
-36.1	8.7		GRAVEL, poorly graded, coarse to medium sand, silt, gray, (GP) 80% shell				10
			Barrel Penetration to 11.0 ft.			-38.4	12.5
			NOTE: 1. Soils are field visually classified in accordance with the Unified Soils Classification System.				15
							17.5
							20
							22.5

Revised 11/9/95