

DRILLING LOG		DIVISION South Atlantic	INSTALLATION Jacksonville District	SHEET 1 OF 1
1. PROJECT MARTIN COUNTY BEACH EROSION		10. SIZE AND TYPE OF BIT Vibracore		
2. LOCATION (Coordinates or Station) X=774,020 Y=1048,999		11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MSL		
3. DRILLING AGENCY Corps of Engineers		12. MANUFACTURER'S DESIGNATION OF DRILL Failing 1500		
4. HOLE NO. (As shown on drawing title and file number) CB-M-3		13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0		
5. NAME OF DRILLER R. Gordon		14. TOTAL NUMBER OF CORE BOXES 1		
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		15. ELEVATION GROUND WATER Tidal		
7. THICKNESS OF BURDEN 0 Ft.		16. DATE HOLE STARTED COMPLETED 8/02/78 8/02/78		
8. DEPTH DRILLED INTO ROCK 0 Ft.		17. ELEVATION TOP OF HOLE -25.0 Ft.		
9. TOTAL DEPTH OF HOLE 20.2 Ft.		18. TOTAL CORE RECOVERY FOR BORING %		
		19. SIGNATURE OF GEOLOGIST D. Rosen		

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC X	SAMPLE NUMBER	REMARKS Bit or Barrel
-25.0	0					-25.0
			SAND, medium to coarse shell grades from much whole shells at top to finer broken shell at 10.1' whole and broken shells, 10.1' to 17.3', gray. (SP)		1	
						VIBRACORE
-42.3	17.3		SAND, very fine to medium, slightly shelly, light gray. (SM)		2	
-45.2	20.2		Note: Soils are field visually classified in accordance with the Unified Soils Classification System.			-45.2