

DRILLING LOG		DIVISION South Atlantic	INSTALLATION Jacksonville District		SHEET OF 1 SHEETS
1. PROJECT Dade County Beach Erosion			10. SIZE AND TYPE OF BIT NA		
2. LOCATION (Coordinates or Station) X=799,229 Y=551,379			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW		
3. DRILLING AGENCY Corps of Engineers			12. MANUFACTURER'S DESIGNATION OF DRILL Vibracore		
4. HOLE NO. (As shown on drawing title and file number) CB-DAC-188			13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN		DISTURBED UNDISTURBED
5. NAME OF DRILLER R. Gordon			14. TOTAL NUMBER CORE BOXES		
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT.			15. ELEVATION GROUND WATER Tidal		16. DATE HOLE STARTED 24 May 78 COMPLETED 24 May 78
7. THICKNESS OF OVERBURDEN			17. ELEVATION TOP OF HOLE -62.0		
8. DEPTH DRILLED INTO ROCK			18. TOTAL CORE RECOVERY FOR BORING 100 %		
9. TOTAL DEPTH OF HOLE 8.0'			19. SIGNATURE OF INSPECTOR Geologist: D. Posen		

ELEVATION a	DEPTH b	LEGEND c	CLASSIFICATION OF MATERIALS (Description) d	% CORE RECOV- ERY e	BOX OR SAMPLE NO. f	REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) g
-62.0	0.0					BIT OR BARREL
-68.4	6.4		SAND, slightly silty, light gray, slightly shelly, fine to coarse, shell sand (SP)		1	VIBRACORE
-70.0	8.0		LIMESTONE, hard gray, composed of cemented shell fragments and coral, numerous solution holes filled with silty sand.			