
















		PROJECT:			CORE NO.:	
		NASSAU COUNTY SAND SEARCH			NCCB-26	
		DRILLER:			DATE OF HOLE:	
		EXMAR			6/92	
		LOGGED BY:			D.A. REP.:	
		F.I.T. N. LaPlace			M. Schroeder	
		DEPTH OF WATER: 24.9'			N= 2,257,554	
		DEPTH OF HOLE: 18.0'			E= 365,494	
ELEVATION	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	% CORE RECOVERY	SAMPLE NO.	REMARKS
	1		MEDIUM GRAY MEDIUM TO COARSE QTZ SAND, POORLY SORTED SHELL MATERIAL 8% SW			
	2					
	3		DARK GRAY MEDIUM QTZ SAND, POORLY SORTED. SHELL MATERIAL 10% SW			
	4		MEDIUM GRAY MEDIUM MUDDY QTZ SAND (SP) TRACE SHELL MATERIAL			
	5		DARK GRAY SHELLY COARSE QTZ SAND, POORLY SORTED SHELL MATERIAL 20% SW			
	6		MEDIUM GRAY COARSE QTZ SAND POORLY SORTED SW SHELL MATERIAL 10%			CUT 6.1'
	7					
	8		MEDIUM GRAY SHELLY COARSE QTZ SAND SHELL MATERIAL 20% SW			
	9		A 2" LAYER OF MUD			
	10					
	11					
	12		LIGHT GRAY MEDIUM GRAINED CLEAN QTZ SAND TRACE SHELL MATERIAL SP			CUT 12.1'
	13					
	14					
	15		LIGHT AND DARK GRAY FINE QTZ SAND INTERBEDDED WITH MUD NO SHELL MATERIAL SC/ML			
	16					
	17					
	18		BOTTOM OF CORE = 18.0'			
	19					
	20					