

DRILLING LOG		DIVISION South Atlantic	INSTALLATION Jacksonville District	SHEET 1 OF 1		
1. PROJECT St. John's Vibracore 1998		10. SIZE AND TYPE OF BIT 3 1/2"				
2. LOCATION (Coordinates or Station) X=415,933 Y=2026,723		11. DAY ON FOR ELEVATION SHOWN (TBM or RSL) MLW				
3. DRILLING AGENCY ANDAMAN & ASSOCIATES, INC.		12. MANUFACTURER'S DESIGNATION OF DRILL Alpine Vibracore				
4. HOLE NO. (As shown on drawing title and file number) CB-SJ98-7		13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0				
5. NAME OF DRILLER O. Hernandez		14. TOTAL NUMBER OF CORE BOXES 0				
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		15. ELEVATION GROUND WATER Tide = -2.2				
7. THICKNESS OF BURDEN 19.6 Ft.		16. DATE HOLE STARTED COMPLETED 8/29/98				
8. DEPTH DRILLED INTO ROCK 0.0 Ft.		17. ELEVATION TOP OF HOLE -17.1 Ft.				
9. TOTAL DEPTH OF HOLE 19.6 Ft.		18. TOTAL CORE RECOVERY FOR BORING 80 %				
		19. SIGNATURE OF GEOLOGIST ROCKLAND BURR				
ELEV.	DEPTH	LOG	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-17.1	0					-17.1
			Sand, fine grained, light gray, trace shell (SP)			
-18.0	1.9					Lat/Lon 29 54 31N 81 15 55W
			Sand, fine grained, light gray (SP)			
						Sieve Analysis Depth USCS 1-1 1/2 SP 9-9 1/2 SP 11 1/2-12 SP 14-14 1/2 SM
-28.1	11.0					
			Sand, fine grained, gray, trace of shell (SP-SM)			
-31.1	14.0					
			Sand, fine grained, dark gray (SP-SM)			
			Lens of silty sand @ 14.0'			
-36.7	19.6					
			End of Boring at 19.6'			
			Soils are field visually classified in accordance with the Unified Soils Classification System.			