

# Boring Designation SLS-09

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1 SHEETS	
1. PROJECT South SLC Offshore Sand Search South St. Lucie Co.				9. SIZE AND TYPE OF BIT			
2. BORING DESIGNATION SLS-09				10. COORDINATE SYSTEM/DATUM Florida State Plane East		HORIZONTAL NAD 1983	
3. DRILLING AGENCY American Vibracore Services				11. MANUFACTURER'S DESIGNATION OF DRILL pneumatic vibracore		<input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER	
4. NAME OF DRILLER AVS				12. TOTAL SAMPLES		DISTURBED UNDISTURBED (UD)	
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				13. TOTAL NUMBER CORE BOXES		14. ELEVATION GROUND WATER	
6. THICKNESS OF OVERBURDEN 0.0 Ft.				15. DATE BORING 12-04-08		STARTED 12-04-08	
7. DEPTH DRILLED INTO ROCK 0.0 Ft.				16. ELEVATION TOP OF BORING -35.4 Ft.		17. TOTAL RECOVERY FOR BORING 18.3 Ft.	
8. TOTAL DEPTH OF BORING 19.2 Ft.				18. SIGNATURE AND TITLE OF INSPECTOR LA			
ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS	
-35.4	0.0						
-36.8	1.4		Medium grained skeletal sand with little fine grained quartz sand fraction. Abrupt contact, grayish brown (2.5Y-5/2), (SP).		1	Sample #1, Depth = 0.5' - 0.8'	
					2	Sample #2, Depth = 4.0' - 4.3'	
					3	Sample #3, Depth = 7.0' - 7.3'	
			Medium grained skeletal sand with little fine grained quartz sand fraction. Thin (~0.2') layers of coarse shell hash throughout. Trace whole shells to 1". Gradational contact, grayish brown (10YR 5/2) to, grayish brown (2.5Y-5/2), (SW).		4	Sample #4, Depth = 9.5' - 9.8'	
					5	Sample #5, Depth = 13.0' - 13.3'	
-51.3	15.9						
-53.8	18.4		Fine grained quartz sand with abundant fine to medium grained shell fragmetns, gray (10YR-5/1), (SP).		6	Sample #6, Depth = 17.0' - 17.3'	
			End of Boring				

FLORIDA DEP ROSS SLC RECON CORES WET SIEVED.GPJ FL DEP ROSS.GDT 09/08/09