

<b>DRILLING LOG</b>		<b>DIVISION</b>	<b>INSTALLATION</b>	<b>SHEET 1</b> <b>OF 1 SHEETS</b>
<b>1. PROJECT</b> 2011 SLC Geotech Investigation St. Lucie County			<b>9. SIZE AND TYPE OF BIT</b>	
<b>2. BORING DESIGNATION</b> SLC-11-A05			<b>10. COORDINATE SYSTEM/DATUM</b> Florida State Plane East	
<b>LOCATION COORDINATES</b> X = 930,994 Y = 1,077,448			<b>HORIZONTAL</b> NAD 1983	
<b>3. DRILLING AGENCY</b> American Vibracore Services			<b>11. MANUFACTURER'S DESIGNATION OF DRILL</b> Pneumatic Vibracore	
<b>CONTRACTOR FILE NO.</b>			<input type="checkbox"/> <b>AUTO HAMMER</b> <input type="checkbox"/> <b>MANUAL HAMMER</b>	
<b>4. NAME OF DRILLER</b> AVS			<b>12. TOTAL SAMPLES</b>	
<b>5. DIRECTION OF BORING</b> <input checked="" type="checkbox"/> <b>VERTICAL</b> <input type="checkbox"/> <b>INCLINED</b>			<b>13. TOTAL NUMBER CORE BOXES</b>	
<b>DEG. FROM VERTICAL</b>			<b>14. ELEVATION GROUND WATER</b>	
<b>BEARING</b>			<b>15. DATE BORING</b> 04-14-11	
<b>6. THICKNESS OF OVERBURDEN</b> 0.0 Ft.			<b>16. ELEVATION TOP OF BORING</b> -37.5 Ft.	
<b>7. DEPTH DRILLED INTO ROCK</b> 0.0 Ft.			<b>17. TOTAL RECOVERY FOR BORING</b> 14.8 Ft.	
<b>8. TOTAL DEPTH OF BORING</b> 17.0 Ft.			<b>18. SIGNATURE AND TITLE OF INSPECTOR</b> LA	

ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS
-37.5	0.0					
			Medium grained skeletal sand with some quartz fraction. Gradational contact, light olive brown (2.5Y-5/3), (SW).		1	Sample #1, Depth = 0.5' - 0.8'
-41.0	3.5					
-41.5	4.0		Medium grained skeletal sand with some quartz fraction and abundant gravel-sized shell fragments. Gradational contact, light brownish gray (2.5Y-6/2), (SW).		2	Sample #2, Depth = 3.5' - 3.8'
			Medium grained skeletal sand with some quartz fraction. Gradational contact, light olive brown (2.5Y-5/3), (SP).		3	Sample #3, Depth = 6.0' - 6.3'
-44.8	7.3				4	Sample #4, Depth = 7.5' - 7.8'
			Medium grained skeletal sand with some quartz fraction and abundant coarse shell hash and some gravel-sized shell. Trace whole shells to 1". Gradational contact, light olive brown (2.5Y-5/3), (SW).			
-48.3	10.8					
			Fine to medium grained quartz sand with abundant fine to medium grained shell fragments. Gradational contact, dark gray (5Y-4/1), (SP).			
-50.0	12.5					
			Medium grained skeletal sand with some quartz fraction. Trace large shell fragments to 1.5", olive gray (5Y-4/2), (SW).			
-52.3	14.8					
			No Recovery.			
-54.5	17.0					
			End of Boring			

FLORIDA DEP ROSS 2011-6-16 SLC PLANS AND SPECS.GPJ FL DEP ROSS.GDT 11/22/11