

<b>DRILLING LOG</b>		<b>DIVISION</b>	<b>INSTALLATION</b>	<b>SHEET 1</b> <b>OF 1 SHEETS</b>
<b>1. PROJECT</b> Walton County Borrow Area A Walton County, Florida			<b>9. SIZE AND TYPE OF BIT</b>	
<b>2. BORING DESIGNATION</b> WA-44			<b>10. COORDINATE SYSTEM/DATUM</b> Florida State Plane North	
<b>LOCATION COORDINATES</b> X = 1,379,293 Y = 478,620			<b>HORIZONTAL</b> NAD 1983	
<b>3. DRILLING AGENCY</b>			<b>11. MANUFACTURER'S DESIGNATION OF DRILL</b> Vibrocure	
<b>CONTRACTOR FILE NO.</b>			<input type="checkbox"/> <b>AUTO HAMMER</b> <input type="checkbox"/> <b>MANUAL HAMMER</b>	
<b>4. NAME OF DRILLER</b> Alpine			<b>12. TOTAL SAMPLES</b>	
<b>5. DIRECTION OF BORING</b> <input checked="" type="checkbox"/> <b>VERTICAL</b> <input type="checkbox"/> <b>INCLINED</b>			<b>13. TOTAL NUMBER CORE BOXES</b>	
<b>DEG. FROM VERTICAL</b>			<b>14. ELEVATION GROUND WATER</b>	
<b>BEARING</b>			<b>15. DATE BORING</b> 08-27-06 10:29	
<b>6. THICKNESS OF OVERBURDEN</b> 0.0 Ft.			<b>16. ELEVATION TOP OF BORING</b> -67.4 Ft.	
<b>7. DEPTH DRILLED INTO ROCK</b> 0.0 Ft.			<b>17. TOTAL RECOVERY FOR BORING</b> 19.7 Ft.	
<b>8. TOTAL DEPTH OF BORING</b> 19.0 Ft.			<b>18. SIGNATURE AND TITLE OF INSPECTOR</b>	

ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS
-67.4	0.0					
					WA-44 0'	Sample #WA-44 0', Depth = 0.0'
					WA-44 1.5'	Sample #WA-44 1.5', Depth = 1.5'
					WA-44 3.0'	Sample #WA-44 3.0', Depth = 3.0'
					WA-44 4.5'	Sample #WA-44 4.5', Depth = 4.5'
					WA-44 6.0'	Sample #WA-44 6.0', Depth = 6.0'
					WA-44 7.5'	Sample #WA-44 7.5', Depth = 7.5'
					WA-44 9.0'	Sample #WA-44 9.0', Depth = 9.0'
-77.2	9.8				WA-44 10.5'	Sample #WA-44 10.5', Depth = 10.5'
-78.2	10.8		Fine sand. Scattered shells at 10' to 10.3', (SP).		WA-44 12.0'	Sample #WA-44 12.0', Depth = 12.0'
			Medium sand. Scattered shells at 11.8' to 12'. Abundant mud-filled burrows at depth of 12.1' to 13', (SP).		WA-44 13.5'	Sample #WA-44 13.5', Depth = 13.5'
-80.4	13.0				WA-44 15.0'	Sample #WA-44 15.0', Depth = 15.0'
-82.6	15.2		Fine sand. Abundant mud-filled burrows at depth of 13' to 13.4', scattered mud-filled burrows at 13.4' to 14.2'. Shells at depth of 13.3' to 13.5', and 14.4' to 14.6', (SP).			
			Carbonate-cemented sediment..			
-87.1	19.7					
			End of Boring			

FLORIDA DEP ROSS WALTON COUNTY DETAIL PHASE II.GPJ FL DEP ROSS.GDT 09/12/07