Hole No. CB-EC-18

CLASS LOC	SOUTH ATLANTIC	JACKSONVILLE DISTRICT	1 of 1 sheets
BOUNDRY CHANNEL, FLORIDA		10. SIZE AND TYPE OF BIT 2" x 3 1/2" x 5'-5' split spoon	
X 237820.61	Y 1194897.02	11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MEAN LOW WATER	
5. CONTRACTOR THOMPSON ENGINEERING TESTING, INC.		12. MANUFACTURER'S DESIGNATION OF DRILL THOMPSON SKID RIG	
6. DIRECTION OF HOLE CB-EC- 18		13. TOTAL NUMBER CORE BOXES 1	
7. NAME OF INSPECTOR K. COLLINS		14. ELEVATION GROUND WATER TIDAL	
8. DIRECTION OF HOLE ☒ VERTICAL ☐ INCLINED ____ DEG. FROM VERT.		15. DATE HOLE STARTED 21 Sept 86 COMPLETED 21 Sept 86	
9. THICKNESS OF OVERBURDEN		16. ELEVATION TOP OF HOLE -8.6	
10. DEPTH DRILLED INTO ROCK		17. TOTAL CORE RECOVERY FOR BORING 41.3 %	
11. TOTAL DEPTH OF HOLE 20.0 FEET		18. SIGNATURE OF INSPECTOR	

ELEVATION	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	CORE RECOVERY	CORE BOX	REMARKS
-8.6	0.0		"GULF OF MEXICO"			-8.6 Blows/FT
	2.5		Tan sand with shell fragments (SP)	50"	1	16 11 67 136
-13.6	5.0					-13.6 175
	7.5		Tan sand (SP)	34	2	26 108 91 167
-18.6	10.0					-18.6 309
	12.5		Tan sand with shell fragments (SP)	44	3	60 140 163 162
-23.6	15.0					-23.6 135
	17.5		Grey sand w/ crushed shell (SP)	37	4	27 38 59 75
-28.6	20.0					-28.6 86

Note: 140 lb. hammer with 18" drop used on 2" I.D. sampler.

0 blS/ft. refers to the number of hammer blows required to advance a 2" sampler (2" I.D. x 2 1/2" O.D.) one foot. The sampler is 5 ft. long and driven continuously 5 ft. where possible.

Blow counts for the 2" sampler have not been correlated with the standard split spoon tests as designated in ASTM D-1586. Judgment is needed in the use of the blow count data for the 2" sampler.

LABORATORY CLASSIFICATION:

SAMPLE #1 SP
2 SP