

DRILLING LOG		DIVISION SOUTH ATLANTIC		Hole No. V-48-94		INSTALLATION MOBILE DISTRICT		SHEET 1 OF 1 SHEETS	
1. PROJECT BAY CO FL OFFSHORE PANAMA CITY BEACHES NOURISHMENT				10. SIZE AND TYPE OF BIT 3.5" x 25' VIBRACORE					
2. LOCATION (Coordinates or Station) ZONE FLN: N 423263 E 1593476				11. ELEVATION DATUM NGVD, FOOT U.S.					
3. DRILLING AGENCY TET, INC.				12. MANUFACTURER'S DESIGNATION OF DRILL VIBRACORE					
4. HOLE NO. (As shown on drawing title and file number) V-48-94				13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN		DISTURBED 7		UNDISTURBED 0	
5. NAME OF DRILLER CHARLIE WESTON				14. TOTAL NUMBER CORE BOXES 0					
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERTICAL				15. ELEVATION GROUNDWATER					
7. THICKNESS OF OVERBURDEN -				16. DATE HOLE		STARTED 27 NOV 94		COMPLETED 28 NOV 94	
8. DEPTH DRILLED INTO ROCK -				17. ELEVATION TOP OF HOLE EL. -33.3					
9. TOTAL DEPTH OF HOLE 18.5 (EL. -51.8)				18. TOTAL CORE RECOVERY FOR BORING 0					
				19. SIGNATURE OF INSPECTOR BRAD RALPH DRAFTED ' CHECKED ' BCR BCR					
ELEVATION <small>a</small>	DEPTH <small>b</small>	LEGEND <small>c</small>	CLASSIFICATION OF MATERIALS (Description) <small>d</small>	% CORE RECOVERY OR W.C. <small>e</small>	BOX OR SAMPLE NO. <small>f</small>	REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) <small>g</small>			
-33.3	0.0								
	3.0		(SP) White medium to fine SAND, trace shell		S-1	LAB: (SP), 1% FINES (FINER THAN #200 SIEVE)			
	6.0				S-2	LAB: (SP), 2% FINES			
-40.3	7.0		(SM) Gray silty fine SAND, trace shell		S-3	LAB: (SP-SM), 11% FINES			
-41.6	8.3		(SC) Gray clayey fine SAND, trace shell		S-4	LAB: (SM), 16% FINES			
-42.1	8.8			100% RECOV					
			(SM) Gray silty medium to fine SAND		S-5	LAB: (SP-SM), 8% FINES			
-45.2	11.9		(CL) Gray medium to fine sandy CLAY						
-45.4	12.1		(SP-SM) Brown medium to fine SAND		S-6	LAB: (SP-SM), 10% FINES			
-46.5	13.2		(OL) Organics/wood						
-46.9	13.6		(SP-SM) Brown medium to fine SAND						
-47.3	14.0		(OL) Organics/wood						
-47.6	14.3								
	15.0		(SP-SM) Gray medium to fine SAND		S-7	LAB: (SP), 5% FINES			
-51.8	18.5								
						B.O.H.			