

DRILLING LOG			DIVISION		INSTALLATION			SHEET 1 OF 1 SHEETS		
1. PROJECT Gulf County Supplemental Port St. Joseph, Florida					9. SIZE AND TYPE OF BIT 2.0 in.					
					10. COORDINATE SYSTEM/DATUM Florida State Plane North		HORIZONTAL NAD 1983		VERTICAL NAVD 88	
2. BORING DESIGNATION RC-20			LOCATION COORDINATES X = 1,677,198. Y = 265,788.29		11. MANUFACTURER'S DESIGNATION OF DRILL <input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER					
3. DRILLING AGENCY			CONTRACTOR FILE NO.		12. TOTAL SAMPLES		DISTURBED		UNDISTURBED (UD)	
4. NAME OF DRILLER Athena					13. TOTAL NUMBER CORE BOXES					
					14. ELEVATION GROUND WATER					
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			DEG. FROM VERTICAL		BEARING		15. DATE BORING		STARTED 07-22-06 COMPLETED 07-22-06	
6. THICKNESS OF OVERBURDEN 0.0 Ft.					16. ELEVATION TOP OF BORING -32.8 Ft.					
7. DEPTH DRILLED INTO ROCK 0.0 Ft.					17. TOTAL RECOVERY FOR BORING 12.4 Ft.					
8. TOTAL DEPTH OF BORING 13.0 Ft.					18. SIGNATURE AND TITLE OF INSPECTOR LA Coastal Geologist					
ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values		% REC.	BOX OR SAMPLE	REMARKS			
-32.8	0.0		Fine grained quartz sand. Abrupt contact, white (10YR-8/1), (SP).			1	Sample #1, Depth = 0.5' - 0.8'			
-36.9	4.1					2				
-45.2	12.4		Muddy, peaty organic-rich fine grained quartz sand. Decreasing organics with depth, black (10YR 2/1) to, brown (10YR-4/3), (SM).							
										End of Boring