

PROJECT: LONGBOAT KEY

CLIENT: ATM

CONTRACTOR: TET

FILE NO. 8102

SHEET NO. 1 of 2

LOCATION:

GROUNDWATER					DEPTH TO:		CASING			SAMPLER		CORE BARREL	
DATE	TIME	WATER	BOTTOM OF CASING	BOTTOM OF HOLE	TYPE:								
3/17	10:25 AM	+0.6			SIZE I.D.:			SPT					
					HAMMER WT.:			1 3/8"					
					HAMMER FALL:			140 #					
								30"					

DATE START: 3-17-89

DATE FINISH: 3-17-89

DRILLER: TAU

INSPECTOR: MBR

DEPTH	SAMP. NO.	CASING BLOWS PER FOOT	SAMPLER BLOWS PER 6 INCHES	SPT BLOWS PER FOOT	STRATA CHANGE	FIELD CLASSIFICATION AND REMARKS
5						WATER DEPTH 15'1" @ 8:30 AM (START) WATER DEPTH 15'10" @ 10:15 AM (FINISH)
10						
15						
15	1		5	14		<del>XXXXXXXXXXXX</del> COMPACT LT. GREY FINE GR. CLEAN SAND
	2		15	14		
			3			
			4			
20	3		10	13	SP	
			6			
			7			
	4		7	11		SAME, TRACE OF SHELL
			4			
			5			
			6			
25	5		10	18		SAME, NO SHELL
			8			
			11			
			5			
	6		5	9		LOOSE GREY VERY FINE GR. SL. SILTY SAND W/ TRACE OF SHELL FRAG.
			4			
			6			
			1			
	7		3	7		LOOSE GREY VERY FINE GR. SL. SILTY SAND & SHELL FRAG.
			4			
			2			
0			3			
			3		SHELL	

ROMWELL & HARRIER, INC.		TEST BORING REPORT				HOLE NO. LB-22	
PROJECT: LONGBOAT KEY						FILE NO. 8102	
CLIENT: ATM						SHEET NO. 2 of 2	
CONTRACTOR: TET						LOCATION:	
GROUNDWATER DEPTH TO:						ELEVATION:	
DATE		TIME		WATER		CASING SAMPLER CORE BARREL	
				BOTTOM OF CASING		TYPE:	
				BOTTOM OF HOLE		SIZE I.D.:	
						HAMMER WT.:	
						HAMMER FALL:	
						SPT	
						1 3/8"	
						140 #	
						30"	
DATE START: 3-17-89						DATE FINISH: 3-17-89	
DRILLER: JAY						INSPECTOR: MBR	
FIELD CLASSIFICATION AND REMARKS							
8 6 SHELL LOOSE SHELL FRAG. W/SOME SILTY GREY VERY FINE GR. SAND							
9 9 SP/SM LOOSE GREYISH - TAN SILT W/SOME SHELL FRAG. & TAN V. FINE GR. SAND.							
10 4 VERY LOOSE, SAME							
BOH @ 35'							
35							
40							
BLOWS/FT. DENSITY BLOWS/FT. CONSISTENCY SAMPLE IDENTIFICATION							
0 - 4 VERY LOOSE 0 - 2 VERY SOFT S _____ SPLIT SPOON							
4 - 10 LOOSE 2 - 4 SOFT T _____ THIN WALL TUBE							
10 - 30 COMPACT/M. DENSE 4 - 8 FIRM U _____ UNDISTURBED PISTON							
30 - 50 DENSE 8 - 15 STIFF O _____ OPEN END ROD							
50 + VERY DENSE 15 - 30 VERY STIFF W _____ WASH SAMPLE							